IN THE CLAIMS

Claims 1-9 (Cancelled).

- 10. (Currently Amended) A solid-electrolyte secondary battery comprising:
- (a) a positive electrode;
- (b) a negative electrode;
- (c) a solid electrolyte comprising a matrix polymer comprising a <u>first</u> fluorocarbon polymer having a weight-average molecular weight of greater than 550,000;
- (d) wherein the matrix polymer further comprises a second fluorocarbon polymer having a weight-average molecular weight of greater than 300,000 and less than 550,000;
- (e) wherein the matrix polymer comprises 30 percent or more by weight of the fluorocarbon polymer having a weight-average molecular weight of greater than 550,000;
- (f) wherein the positive electrode has a face which is directed towards the negative electrode and the solid-electrolyte layer is formed on the face of the positive electrode and impregnates into the face a solution in which the solid electrolyte is dissolved; and
- (g) wherein the negative electrode has a face directed toward the positive electrode and the solid-electrolyte layer is formed on the face and impregnates into the face a solution in which the solid electrolyte is dissolved.

Claims 11-12 (Cancelled).

- 13. (Currently Amended) The solid-electrolyte secondary batter of claim 10, wherein the <u>first</u> fluorocarbon polymer is one of a polyvinylidene fluoride and <u>or</u> a polyvinylidene fluoride/hexafluoropropylene copolymer.
- 14. (Previously Presented) The solid-electrolyte secondary battery of Claim 10 wherein at least one of the positive and negative electrodes comprises a binder comprising the matrix polymer of the solid electrolyte.

Response to May 13, 2004 Final Office Action Application No. 09/446,641

Page 3

- 15. (Previously Presented) The solid-electrolyte secondary battery of Claim 10 wherein the negative electrode comprises a material which is capable of intercalating or deintercalating a lithium ion.
- 16. (Previously Presented) The solid-electrolyte secondary battery of Claim 15 wherein the material which is capable of intercalating or deintercalating a lithium ion comprises a carbon material.
- 17. (Previously Presented) The solid-electrolyte secondary battery of Claim 10, wherein the positive electrode comprises a composite oxide of lithium and a transition metal.

Claims 18-19 (Cancelled).

- 20. (Currently Amended) The solid-electrolyte secondary battery of Claim 10, wherein the solid electrolyte comprises a first fluorocarbon polymer having has a weight-average molecular weight of 1,000,000 or more.
- 21. (Currently Amended) The solid-electrolyte secondary battery of Claim 10, wherein the solid-electrolyte comprises a first fluorocarbon polymer having has a weight-average molecular weight of between 1,000,000 and 3,000,000.
 - 22. (Currently Amended) A battery comprising:
 - a positive electrode;
 - a negative electrode; and
- a solid electrolyte provided between the positive electrode and the negative electrode, the solid electrolyte comprising a <u>first</u> fluorocarbon polymer having a weight-average molecular weight of greater than 550,000.

Response to May 13, 2004 Final Office Action Application No. 09/446,641

Page 4

- 23. (Previously Presented) The battery of claim 22, wherein the solid electrolyte further comprises a second fluorocarbon polymer having a weight-average molecular weight of greater than 300,000 and less than 550,000.
- 24. (Previously Presented) The battery of claim 23, wherein the solid electrolyte comprises 30 percent or more by weight of the fluorocarbon polymer having a weight-average molecular weight of greater than 550,000.
- 25. (Previously Presented) The battery of claim 22, wherein the positive electrode has a face which is directed towards the negative electrode and the solid-electrolyte layer is formed on the face of the positive electrode and impregnates into the face a solution in which the solid electrolyte is dissolved.
- 26. (Previously Presented) The battery of claim 22, wherein the negative electrode has a face directed toward the positive electrode and the solid-electrolyte layer is formed on the face and impregnates into the face a solution in which the solid electrolyte is dissolved.
- 27. (Currently Amended) The solid-electrolyte secondary battery of Claim 22, wherein the solid electrolyte comprises a first fluorocarbon polymer having has a weight-average molecular weight of 1,000,000 or more.
- 28. (Currently Amended) The solid-electrolyte secondary battery of Claim 22, wherein the solid electrolyte comprises a <u>first</u> fluorocarbon polymer having <u>has</u> a weight-average molecular weight of between 1,000,000 and 3,000,000.